




Service Engines and Accessories






3.5 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER/TRIMMER APPLICATIONS

| MODEL | LEV80 |
|------------------|---------------------------------------|
| HORSEPOWER | 3.5 2.61 kW |
| BORE & STROKE | 2.312 x 1.844 in. 58.73 x 46.84 mm |
| DISPLACEMENT | 7.75 cu. in. 128 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 18.75 lbs. 8.5 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- Lightweight L-head design.
- Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- Aluminized muffler protects against rust and keeps engine quieter, longer.
- Mechanical governor for instant response to changing load conditions.
- Certified to EPA Phase II, CARB Tier II standards.
- Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|-------------|----------|-----------------------------|-------------|---|---------------|----------------------------|-----------------------------------|--------------------|------|
| 804190 | MTD | 37313 | Fixed Speed | 37116/37117 (Poly) Ref. 1 | Side & Bottom | 1 qt. (.95 ltr.) Ref. 2 | 36559A (Reverse Pull) | 3400 | |





3.5 - 4.5 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER/TRIMMER APPLICATIONS

| | |
|------------------|--------------------------------------|
| MODEL | LV148EA, LEV90 |
| HORSEPOWER | 3.5 - 4.5 2.61 - 3.36 kW |
| BORE & STROKE | 2.50 x 1.844 in. 63.50 x 46.84 mm |
| DISPLACEMENT | 9.03 cu. in. 148 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 18.75 lbs. 8.5 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- † Lightweight L-head design.
- † Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- † Aluminized muffler protects against rust and keeps engine quieter, longer.
- † Mechanical governor for instant response to changing load conditions.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|-------------|----------|-----------------------------|-------------|---|---------------|------------------------------|-----------------------------------|--------------------|------|
| 804193 | MTD | 37810 | Fixed Speed | 35066 (Paper) Ref. 1 | Side & Bottom | 1.25 qt. (1.19 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3200 | |
| 804220 | MTD | 37821 | Fixed Speed | 35066 (Paper) Ref. 1 | Side & Bottom | 1.25 qt. (1.19 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3200 | |




6.0 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER APPLICATION

| MODEL | LEV105 |
|------------------|---------------------------------------|
| HORSEPOWER | 6.0 4.47 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.90 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 18.75 lbs. 8.5 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- † Lightweight L-head design.
- † Patented Easy Start Performance (ESP) technology ensures easy starting.
- † Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- † Aluminized muffler protects against rust and keeps engine quieter, longer.
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † Automotive-style paper element air filter gives you superior engine performance and protection.
- † High oil fill with automotive-type dipstick.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|-------------|----------|-----------------------------|-------------|---|---------------|----------------------------|-----------------------------------|--------------------|------|
| 805189 | MTD | 37785 | Fixed Speed | 36905 (Paper) Ref. 1 | Side & Bottom | 1 qt. (.95 ltr.) Ref. 2 | 36559A (Reverse Pull) | 3300 | |

MTD shroud not included.





6.0 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LV195EA, LEV120 |
| HORSEPOWER | 6.0 4.47 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.90 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 18.75 lbs. 8.5 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- ▮ Lightweight L-head design.
- ▮ Patented Easy Start Performance (ESP) technology ensures easy starting.
- ▮ Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- ▮ Aluminized muffler protects against rust and keeps engine quieter, longer.
- ▮ Premium mechanical governor provides positive, instant response to changing load conditions.
- ▮ Automotive-style paper element air filter gives you superior engine performance and protection.
- ▮ High oil fill with automotive-type dipstick.
- ▮ Certified to EPA Phase II, CARB Tier II standards.
- ▮ Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|----------------|----------|-----------------------------|----------------|---|-----------|----------------------------|-----------------------------------|--------------------|------|
| 806167B | Toro | 37478 | Remote Snap-In | 35066 (Paper) Ref. 1 | Bottom | 1 qt. (.95 ltr.) Ref. 2 | 36559A (Reverse Pull) | 3200 | |
| 806780 | Standard | 37479 | Fixed Speed | 36905 (Paper) Ref. 1 | Bottom | 1 qt. (.95 ltr.) Ref. 2 | 36559A (Reverse Pull) | 3200 | |






6.5 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LV195EA, LEV120 |
| HORSEPOWER | 6.5 4.47 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.90 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 18.75 lbs. 8.5 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- † Lightweight L-head design.
- † Patented Easy Start Performance (ESP) technology ensures easy starting.
- † Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- † Aluminized muffler protects against rust and keeps engine quieter, longer.
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † Automotive-style paper element air filter gives you superior engine performance and protection.
- † High oil fill with automotive-type dipstick.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|-------------|----------|-----------------------------|-------------|---|-----------|------------------------------|-----------------------------------|--------------------|------|
| 806173A | Toro | 37692 | Fixed Speed | 36905 (Paper) Ref. 1 | Bottom | 1.25 qt. (1.19 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3050 | † |
| 806174A | Toro | 37692 | Fixed Speed | 36905 (Paper) Ref. 1 | Bottom | 1 qt. (.95 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3050 | * † |
| 806175 | Service | 37507 | Manual | 35066 (Paper) Ref. 1 | Bottom | 1.25 qt. (1.19 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3750 | |
| 806708C | Standard | 37519 | Remote | 36905 (Paper) Ref. 1 | Bottom | 1.25 qt. (1.19 ltrs.) Ref. 2 | | 3750 | ▲ |

* Equipped with electric starter motor.
† Plastic shroud not included.

▲ Heavy Flywheel







6.5 HORSEPOWER SMALL FRAME ROTARY LAWN MOWER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OVRM120 |
| HORSEPOWER | 6.5 4.47 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.90 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 25.75 lbs. 11.6 kg |
| BOLT MTG. CIRCLE | 8 in. 203 mm |



FEATURES

- ï Lightweight L-head design.
- ï Patented Easy Start Performance (ESP) technology ensures easy starting.
- ï Full pressure lubrication system keeps all critical areas supplied with oil for longer engine life.
- ï Aluminized muffler protects against rust and keeps engine quieter, longer.
- ï Premium mechanical governor provides positive, instant response to changing load conditions.
- ï Automotive-style paper element air filter gives you superior engine performance and protection.
- ï High oil fill with automotive-type dipstick.
- ï Certified to EPA Phase II, CARB Tier II standards.
- ï Two-year warranty.




| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Compliance Brake Service Part No. | Top Governed Speed | Note |
|----------------|----------------------------|-----------------------------|----------------|---|---------------|-----------------------------|-----------------------------------|--------------------|------|
| 806163D | Snapper | 37520 | Remote Snap-In | 36905 (Paper) Ref. 1 | Side & Bottom | 1.5 qt. (1.43 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3450 | |
| 806168B | Murray Home Depot - Scotts | 37522 | Manual Control | 36905 (Paper) Ref. 1 | Side & Bottom | 1.5 qt. (1.43 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3200 | |
| 806169 | Murray | 37201 | Manual Control | 36905 (Paper) Ref. 1 | Side & Bottom | 1.5 qt. (1.43 ltrs.) Ref. 2 | 36559A (Reverse Pull) | 3200 | * |

* 8-1/2:1 Auxiliary P.T.O.




8.0 HORSEPOWER RIDER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | TVM220 |
| HORSEPOWER | 8.0 5.97 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 32 oz. .94 ltr. |
| (APPROX.) WEIGHT | 57 lbs. 25.9 kg |
| BOLT MTG. CIRCLE | 8 & 10 in. 203 mm & 254 mm |



FEATURES

- † Cast Iron Cylinder Sleeve.
- † Ultra-Balance^{AE} System.
- † Paper Kleen-Aire System with Pre-Filter.
- † Float Carburetor with Choke.
- † Aluminized Muffler with Catalyst.
- † Mechanical Governor.
- † Electronic CDI Ignition.
- † Positive Displacement Oil Pump.
- † Oil Fill Tube with Dipstick.
- † Mechanical Compression Release.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-----------------|-------------------|-------------------------------|---|------------|---------------------------------|--------------------|
| 808770C | Snapper | 35422A | 3 Amp D.C. | Remote | †Electric Provisions w/Rewind | 35403 (Paper) 35404 (Poly) Ref. 5 | Side | None | 3400 |
| 808771D | Toro | 35422A | 3 Amp D.C. | Remote | Electric Starter w/o Rewind | 35403 (Paper) 35404 (Poly) Ref. 5 | Dual Sides | None | 3350 |
| 808772C | Ariens | 35422A | 3 Amp D.C. | Remote w/Override | Electric Starter w/Rewind | 35403 (Paper) 35404 (Poly) Ref. 5 | Side | 3 qt. (2.85 ltrs.) Ref. 3 | 3250 |

Ü 36680 - 12 Volt electric starter can be installed.
 33635C - Blower housing is needed to mount recoil starter.
 NOTE: For replacements requiring 7/8" (22.22) diameter crankshaft, order 37660.




10.0 HORSEPOWER RIDER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | TVM220 |
| HORSEPOWER | 10.0 7.46 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 32 oz. .94 ltr. |
| (APPROX.) WEIGHT | 57 lbs. 25.9 kg |
| BOLT MTG. CIRCLE | 8 & 10 in. 203 mm & 254 mm |



FEATURES

- † Low emission overhead valve design.
- † KLEEN-AIRE[®] intake air cleaning system with paper air filter means less engine wear.
- † Large 1.375" main bearings for smooth, long life.
- † Ultra-Balance[®] low vibration system.
- † 12 Volt electric starter.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-----------------|-------------------|-----------------------------|---|-----------|---------------------------------|--------------------|
| 810762C | Murray | 35429A | 3 Amp D.C. | Remote | Electric Starter w/o Rewind | 35403 (Paper) 35404 (Poly) Ref. 5 | Side | 3 qt. (2.85 ltrs.) Ref. 3 | 3400 |
| 810763C | Murray | 35429A | 3 Amp D.C. | Remote w/Override | Electric Starter w/o Rewind | 35403 (Paper) 35404 (Poly) Ref. 5 | Side | 3 qt. (2.85 ltrs.) Ref. 3 | 3400 |

33635C - Blower housing is needed to mount recoil starter composite with 8 studs.

NOTE: For replacements requiring 7/8" (22.22) diameter crankshaft, order 37660.




13.0, 13.5 HORSEPOWER OVERHEAD VALVE RIDER APPLICATION

| | |
|------------------|---|
| MODEL | OV358EA, OHV130-135 |
| HORSEPOWER | 13.0, 13.5 9.69 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 32 oz. 39 oz. w/oil filter .95 ltr. 1.17 ltrs. |
| (APPROX.) WEIGHT | 64 lbs. 28.8 kg |
| BOLT MTG. CIRCLE | 8 & 10 in. 203 mm & 254 mm |



FEATURES

- Low emission overhead valve design.
- KLEEN-AIRE[®] intake air cleaning system with paper air filter means less engine wear.
- Large 1.375" main bearings for smooth, long life.
- Ultra-Balance[®] low vibration system.
- 12 Volt electric starter.
- Certified to EPA Phase II, CARB Tier II standards.
- Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Top Governed Speed | Notes |
|----------------|----------|-----------------------------|--------------------------|----------|------------------|---|-----------|--------------------|-------|
| 813700B | MTD | 36924 | 3 Amp D.C. 5 Amp A.C. | Remote | Electric Starter | 36356 (Paper) 36357 (Poly) Ref. 5 | Side | 3250 | ● ▲ * |
| 813701D | Swisher | 36924 | 3 Amp D.C. | Remote | Electric Starter | 36356 (Paper) 36357 (Poly) Ref. 5 | Side | 3600 | ▲ * |

- Muffler omitted
- ▲ Fuel tank omitted
- * Rotary pump with oil filter.





18.0 HORSEPOWER OVERHEAD VALVE RIDER APPLICATION

| | | |
|------------------|-------------------------------------|---------------------|
| MODEL | OV490EA, OHV180 | |
| HORSEPOWER | 18.0 | 13.4 kW |
| BORE & STROKE | 3.562 x 3.00 in. 90.48 x 76.6 mm | |
| DISPLACEMENT | 29.9 cu. in. 490 cc | |
| OIL CAPACITY | 55 oz. | 62 oz. w/oil filter |
| (APPROX.) WEIGHT | 75 lbs. | 33.8 kg |
| BOLT MTG. CIRCLE | 10 in. | 254 mm |



FEATURES

- † Automotive-style Gerotor pump lubrication keeps all bearing areas supplied with oil for longer engine life.
- † Extra large 1.625" main bearings for smooth, long life.
- † KLEEN-AIRE[®] intake air cleaning system with a paper air filter means less engine wear.
- † Vertical crankshaft with counterclockwise rotation when viewed from power take-off end.
- † 12 Volt electric starter.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|--------------------|-----------------------------|----------------------------|----------|--------------------------------|---|-----------|----------------------------|--------------------|
| 818500A | Service Dual CB* | 36512 | 3 Amp D.C. 5 Amp A.C. | Remote | Electric Starter w/o Rewind | 36356 (Paper) 36357 (Poly) Ref. 5 | Side | None | 3450 |
| 818501A | Service Single CB* | 36308 | 16 Amp D.C. w/Regulator | Remote | Electric Starter w/o Rewind | 36356 (Paper) 36357 (Poly) Ref. 5 | Side | None | 3450 |

CB Counterbalance

* 36435A - Oil filter can be installed.





22.0 HORSEPOWER OVERHEAD VALVE RIDER APPLICATION

| | |
|------------------|--|
| MODEL | OV691EA, TVT691 |
| HORSEPOWER | 22.0 16.4 kW |
| BORE & STROKE | 3.125 x 2.75 in. 79.38 x 69.85 mm |
| DISPLACEMENT | 42.18 cu. in. 691 cc |
| OIL CAPACITY | 72 oz. 80 oz. w/oil filter 2.16 ltrs. 2.4 ltrs. |
| (APPROX.) WEIGHT | 90 lbs. 40.5 kg |
| BOLT MTG. CIRCLE | 10 in. 254 mm |



FEATURES

- Smooth, low vibration twin cylinder power.
- Automotive-style Gerotor oil pump lubrication system keeps all bearing areas supplied with oil for longer engine life.
- Dual carburetors.
- Vertical crankshaft with counterclockwise rotation when viewed from power take-off end.
- 12 Volt electric starter.
- Certified to EPA Phase II, CARB Tier II standards.
- Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|----------------------------|----------|-----------------------------|---|-----------|----------------------------|--------------------|
| 822500A | Standard | 37371 | 3 Amp D.C. 5 Amp A.C. | Remote | Electric w/o Rewind | 37360 (Paper) Ref. 7 | Side | None | 3350 |
| 822502 | MTD | 37371 | 16 Amp D.C. w/Regulator | Remote | Electric w/o Rewind | 37360 (Paper) 37361 (Poly) Ref. 7 | Side | None | 3450 |
| 825500A | MTD | 37818 | 16 Amp D.C. w/Regulator | Remote | Electric Starter w/o Rewind | 37360 (Paper) 37361 (Poly) Ref. 7 | Side | None | 3450 |




3.0 HORSEPOWER TILLER APPLICATION

| | |
|------------------|--------------------------------------|
| MODEL | H30 |
| HORSEPOWER | 3.0 2.24 kW |
| BORE & STROKE | 2.50 x 1.844 in. 63.51 x 46.84 mm |
| DISPLACEMENT | 9.06 cu. in. 148 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 25 lbs. 11.34 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- ï Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- ï Soft-pull recoil starter for easy starts.
- ï Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- ï Aluminized muffler resists corrosion so engine remains quieter longer.
- ï Certified to EPA Phase II, CARB Tier II standards.
- ï Two-year warranty.




| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Exhaust Direction | Fuel Tank (pg. 3) Ref.No. | Top Governed Speed Ref. No. |
|----------------|------------|-----------------------------|---------------------------|---|------------|-------------------|---------------------------|-----------------------------|
| 903666A | Garden Way | 37303 | Remote/Manual Convertible | 30727 (Paper) Ref. 1 | Dual Sides | PTO Side | 2 qt. (1.89 ltrs.) Ref. 5 | 3750 |





3.5 HORSEPOWER TILLER APPLICATION

| | |
|------------------|--------------------------------------|
| MODEL | H35 |
| HORSEPOWER | 3.5 2.61 kW |
| BORE & STROKE | 2.50 x 1.938 in. 63.51 x 49.23 mm |
| DISPLACEMENT | 9.52 cu. in. 156 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 25 lbs. 11.34 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- † Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- † Soft-pull recoil starter for easy starts.
- † Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- † Aluminized muffler resists corrosion so engine remains quieter longer.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Exhaust Direction | Top Governed Speed | Note |
|----------------|------------|-----------------------------|---------------------------|---|------------|----------------------------|-------------------|--------------------|------|
| 903668A | Garden Way | 34734A | Remote/Manual Convertible | 30727 (Paper) Ref. 1 | Dual Sides | 2 qt. (1.89 ltrs.) Ref. 4 | PTO Side | 3750 | † |

Ü 2:1 Extended camshaft.




3.5 HORSEPOWER MINI-BIKE APPLICATION

| | |
|------------------|--------------------------------------|
| MODEL | H35 |
| HORSEPOWER | 3.5 2.61 kW |
| BORE & STROKE | 2.50 x 1.938 in. 63.51 x 49.23 mm |
| DISPLACEMENT | 9.52 cu. in. 156 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 25 lbs. 11.34 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- ï Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- ï Soft-pull recoil starter for easy starts.
- ï Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- ï Aluminized muffler resists corrosion so engine remains quieter longer.
- ï Certified to EPA Phase II, CARB Tier II standards.
- ï Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Exhaust Direction | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|--------------------|---|------------|-------------------|---------------------------------|--------------------|
| 903451B | Standard | 34734A | Mini-Bike (Remote) | 30727 (Paper) 35974 (Poly) Ref. 1 | Dual Sides | Carb. Side | 2 qt. (1.89 ltrs.) Ref. 4 | 4000 |




4.0 HORSEPOWER MINI-BIKE APPLICATION

| | |
|------------------|--------------------------------------|
| MODEL | H40 |
| HORSEPOWER | 4.0 2.61 kW |
| BORE & STROKE | 2.50 x 1.938 in. 63.51 x 49.23 mm |
| DISPLACEMENT | 9.52 cu. in. 156 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 25 lbs. 11.34 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- ï Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- ï Soft-pull recoil starter for easy starts.
- ï Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- ï Aluminized muffler resists corrosion so engine remains quieter longer.
- ï Certified to EPA Phase II, CARB Tier II standards.
- ï Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Exhaust Direction | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|--------------------|---|------------|-------------------|---------------------------------|--------------------|
| 904416B | Standard | 34735 | Mini-Bike (Remote) | 30727 (Paper) 35974 (Poly) Ref. 1 | Dual Sides | Carb. Side | 2 qt. (1.89 ltrs.) Ref. 4 | 4000 |








5.0 HORSEPOWER WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LH195SA, HSSK50 |
| HORSEPOWER | 5.0 3.73 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.88 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 33 lbs. 15.0 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- ï Manual choke and easy start primer give fast, reliable starts on the coldest days.
- ï Winter Engineered^{FE} to prevent ice buildup and engine shut downs.
- ï Premium mechanical governor provides positive, instant response to changing load conditions.
- ï High oil fill with automotive-type dipstick.
- ï Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Provisions for Electric Starter | Controls | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed | Note |
|----------------|----------|-----------------------------|---------------------------------|---------------------------|--------------------|----------------------------|--------------------|------|
| 905363B | MTD | 35975 | X * | Remote/Manual Convertible | Dual Sides & Front | 2 qt. (1.89 ltrs.) Ref. 4 | 3750 | † |
| 905364A | Standard | 34740 | X * | Remote/Manual Convertible | Dual Sides & Front | 2 qt. (1.89 ltrs.) Ref. 4 | 3750 | † |
| 905365 | Standard | 35975 | X * | Remote/Manual Convertible | Dual Sides & Front | 2 qt. (1.89 ltrs.) Ref. 4 | 3750 | † |
| 905367 | Murray | 37245 | X * | Remote/Manual Convertible | Dual Sides & Front | 2 qt. (1.89 ltrs.) Ref. 4 | 3750 | |

* 33290E - 120 Volt electric starter can be installed.
Ü 2:1 Extended camshaft.




5.5 HORSEPOWER OVERHEAD VALVE UTILITY APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH195EA, OHH55 |
| HORSEPOWER | 5.5 4.10 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.88 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 30 lbs. 13.5 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- Soft-pull recoil starter for easy starts.
- Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- Aluminized muffler resists corrosion so engine remains quieter longer.
- KLEEN-AIRE^{AE} filtration system pre-cleans air for superior performance and extended life.
- Certified to EPA Phase II, CARB Tier II standards.
- Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|-------------|----------|-----------------------------|---------------------------|---|-------------------|----------------------------|--------------------|
| 905242D | Standard | 34740 | Manual/Remote Convertible | 36046 (Paper) Ref. 1 | Dual Side & Front | 3 qt. (2.85 ltrs.) Ref. 4 | 3750 |







6.0 HORSEPOWER OVERHEAD VALVE VARIOUS APPLICATIONS

| | |
|------------------|---------------------------------------|
| MODEL | OH195EA, OHH60 |
| HORSEPOWER | 6.0 4.10 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.88 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 30 lbs. 13.5 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- † Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- † Soft-pull recoil starter for easy starts.
- † Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- † Aluminized muffler resists corrosion so engine remains quieter longer.
- † KLEEN-AIRE[®] filtration system pre-cleans air for superior performance and extended life.
- † Certified to EPA Phase II, CARB Tier II standards.
- † Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-------------|---|-------------------|------------------------------|--------------------|
| 906221C | Murray | 37188 | RV Control | 36046 (Paper) 36634 (Poly) Ref. 1 | Dual Side & Front | 3 qt. (2.85 ltrs.) Ref. 4 | 3350 |
| 906222B | Generac | 34745 | Fixed Speed | 36046 (Paper) Ref. 1 | Dual Side & Front | 3 qt. (2.85 ltrs.) Ref. 4 | 3900 |
| 906223D | Murray | 36483 | RV Control | 36046 (Paper) 36634 (Poly) Ref. 1 | Dual Side & Front | 3 qt. (2.85 ltrs.) Ref. 4 | 3350 |
| 906604 | MTD | 34746 | Manual | 36046 (Paper) Ref. 1 | Dual Side & Front | 3 qt. (2.85 ltrs.) Ref. 4 | 3750 |







7.0 HORSEPOWER OVERHEAD VALVE WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH195SA, OHSK70 |
| HORSEPOWER | 7.0 5.22 kW |
| BORE & STROKE | 2.795 x 1.938 in. 70.99 x 49.23 mm |
| DISPLACEMENT | 11.88 cu. in. 195 cc |
| OIL CAPACITY | 21 oz. .62 ltr. |
| (APPROX.) WEIGHT | 30 lbs. 13.5 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES

- † Manual choke and easy start primer give fast, reliable starts on the coldest days.
- † Winter Engineered^Æ to prevent ice buildup and engine shut downs.
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † High oil fill with automotive-type dipstick.
- † Two-year warranty with ten years on electronic ignition.




| Part Number | Customer | Crankshaft Service Part No. | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed | Note |
|----------------|----------|-----------------------------|----------|---------------------------------|--------------------|--------------------------------|--------------------|------|
| 907364B | MTD | 35975 | Manual | X * | Front Dual Side | 3.5 qt. (3.33 ltrs.) Ref. 4 | 3750 | † |
| 907365C | Standard | 34739 | Manual | X * | Front Dual Side | 3.5 qt. (3.33 ltrs.) Ref. 4 | 3750 | |
| 907366A | Standard | 34740 | Manual | X * | Front Dual Side | 3.5 qt. (3.33 ltrs.) Ref. 4 | 3750 | |

* 33290E - 120 Volt electric starter kit can be installed.
Ü 2:1 extended camshaft







9.0 HORSEPOWER WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LH318SA, HMSK90 |
| HORSEPOWER | 9.0 5.97 kW |
| BORE & STROKE | 3.125 x 2.532 in. 79.38 x 64.31 mm |
| DISPLACEMENT | 19.43 cu. in. 318 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 55 lbs. 25.0 kg |
| BOLT MTG. CIRCLE | 3.625 & 5 in. 90 mm & 130 mm |



FEATURES

- ï Manual choke and easy start primer give fast, reliable starts on the coldest days.
- ï Winter Engineered^Æ to prevent ice buildup and engine shut downs.
- ï Cast iron cylinder sleeve for extended engine life. (Enduro^Æ XL only)
- ï Premium mechanical governor provides positive, instant response to changing load conditions.
- ï High oil fill with automotive-type dipstick.
- ï Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|-------------|----------|-----------------------------|-----------------|----------|---------------------------------|-----------------|----------------------------|--------------------|
| 909300A | Standard | 35372A | 3 Amp A.C. | Manual | x * | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3450 |
| 909301A | Standard | 35443A | | Manual | x * | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3250 |
| 909303B | MTD † | 35980A | 18 Watt | Manual | x * | Front Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 |

* 33329E - 120 Volt electric starter can be installed.

Ü 2:1 Extended camshaft




9.0 HORSEPOWER OVERHEAD VALVE WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH318SA, OHSK90 |
| HORSEPOWER | 9.0 6.71 kW |
| BORE & STROKE | 3.125 x 2.532 in. 79.38 x 64.31 mm |
| DISPLACEMENT | 19.43 cu. in. 318 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 60 lbs. 27.2 kg |
| BOLT MTG. CIRCLE | 3.625 & 5 in. 90 mm & 130 mm |



FEATURES

- † Manual choke and easy start primer give fast, reliable starts on the coldest days.
- † Winter Engineered^{FE} to prevent ice buildup and engine shut downs.
- † Cast iron cylinder sleeve for extended engine life. (Enduro^{FE} XL only)
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † High oil fill with automotive-type dipstick.
- † Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-----------------|----------|---------------------------------|-----------|-----------------------------|--------------------|
| 909302B | Standard | 37252 | 18 Watt | Manual | X * | Dual Side | 1 Gallon (3.8 ltrs.) Ref. 9 | 3600 |

* 33329E - 120 Volt electric starter can be installed.







10.0 HORSEPOWER MEDIUM FRAME

| | |
|------------------|---------------------------------------|
| MODEL | HM100 |
| HORSEPOWER | 10.0 7.46 kW |
| BORE & STROKE | 3.125 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 56 lbs. 25.45 kg |
| BOLT MTG. CIRCLE | 3.625 & 5 in. 90 mm & 130 mm |



FEATURES

- Soft-pull recoil starter for easy starts.
- Electronic capacitor discharge ignition (CDI) system for easy starting, even at low pulling speeds.
- Polyethylene fuel tank prevents rust and features a large, easy-fill opening.
- Aluminized muffler resists corrosion so engine remains quieter longer.
- Certified to EPA Phase II, CARB Tier II standards.
- Two-year warranty.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Starter | Air Cleaner Style (pg. 2) Service Part No. | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|---------------|-----------------------------|-----------------|-------------|--------------------------------|--|-----------|---------------------------------|--------------------|
| 910206B | MTD Ltd. BB | 35420A | | Manual | Rewind | 34700B (Paper) 34703 (Poly) Ref. 4 | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3400 |
| 910207B | Standard | 35372A | | Manual | * Electric Provisions w/Rewind | 33268 (Paper) Ref. 1 | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 |
| 910263D | Coleman ▲ | 35441A | | Fixed Speed | * Electric Provisions w/Rewind | 34700B (Paper) 34703 (Poly) Ref. 4 | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 |
| 910265D | Devilbiss Ü ▲ | 37302 | | Fixed Speed | Rewind | 34700B (Paper) 34703 (Poly) Ref. 4 | Dual Side | None | 3750 |

* 36680 - 12 Volt electric starter can be installed.
 Ü Low oil shutdown.
 ▲ Climate guard.
 BB Ball Bearing







11.0 HORSEPOWER WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LH358SA, HMSK110 |
| HORSEPOWER | 11.0 7.46 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 56 lbs. 25.45 kg |
| BOLT MTG. CIRCLE | 3.625 90 mm |



FEATURES

- † Manual choke and easy start primer give fast, reliable starts on the coldest days.
- † Winter Engineered^Æ to prevent ice buildup and engine shut downs.
- † Cast iron cylinder sleeve for extended engine life. (Enduro^Æ XL only)
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † High oil fill with automotive-type dipstick.
- † Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed | Notes |
|-------------|----------|-----------------------------|-----------------|----------|-----------|----------------------------|--------------------|-------|
| 911300B | Standard | 36245 | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3450 | * † |
| 911301B | Standard | 35443A | 3 Amp A.C. | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3250 | * |
| 911304B | Standard | 36245 | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 | * |
| 911305B | Standard | 35443A | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3450 | * |
| 911307 | Standard | 37231 | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 | * |

* 33329E - 120 volt electric starter can be installed.

Ü 2:1 extended camshaft







11.0 HORSEPOWER WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | LH358SA, HMSK110 |
| HORSEPOWER | 11.0 7.46 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 56 lbs. 25.45 kg |
| BOLT MTG. CIRCLE | 3.625 90 mm |



FEATURES

- † Manual choke and easy start primer give fast, reliable starts on the coldest days.
- † Winter Engineered^Æ to prevent ice buildup and engine shut downs.
- † Cast iron cylinder sleeve for extended engine life. (Enduro^Æ XL only)
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † High oil fill with automotive-type dipstick.
- † Two-year warranty with ten years on electronic ignition.




| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed | Notes |
|----------------|----------|-----------------------------|-----------------|----------|-----------|---------------------------------|--------------------|-------|
| 911302B | Standard | 35372A | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3450 | * |
| 911303B | Standard | 35372A | 3 Amp A.C. | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3450 | * |
| 911360B | MTD LTD. | 35980A | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 | * † |
| 911361B | Standard | 35980A | 18 Watt | Manual | Dual Side | 4 qt. (3.79 ltrs.) Ref. 4 | 3600 | * † |

* 33329E - 120 Volt electric starter can be installed.
 Ü 2:1 extended camshaft




11.0 HORSEPOWER OVERHEAD VALVE WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH318SA, OHSK110 |
| HORSEPOWER | 11.0 8.20 kW |
| BORE & STROKE | 3.125 x 2.532 in. 79.38 x 64.31 mm |
| DISPLACEMENT | 19.43 cu. in. 318 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 60 lbs. 27.2 kg |
| BOLT MTG. CIRCLE | 5 & 6.5 in. 130 mm & 170 mm |



FEATURES

- Manual choke and easy start primer give fast, reliable starts on the coldest days.
- Winter Engineered^Æ to prevent ice buildup and engine shut downs.
- Cast iron cylinder sleeve for extended engine life. (Enduro^Æ XL only)
- Premium mechanical governor provides positive, instant response to changing load conditions.
- High oil fill with automotive-type dipstick.
- Two-year warranty with ten years on electronic ignition.




| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|-------------|----------|-----------------------------|-----------------|----------|---------------------------------|-----------|-----------------------------|--------------------|
| 911306C | Standard | 37252 | 18 Watt | Manual | X * | Dual Side | 1 Gallon (3.8 ltrs.) Ref. 9 | 3600 |

* 33329E - 120 Volt electric starter can be installed.




12.0 HORSEPOWER OVERHEAD VALVE WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH358SA, OHSK120 |
| HORSEPOWER | 12.0 8.95 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in.. 358 cc |
| OIL CAPACITY | 26 oz. .77 ltr. |
| (APPROX.) WEIGHT | 60 lbs. 27.2 kg |
| BOLT MTG. CIRCLE | 5 & 6.5 in. 130 mm & 170 mm |



FEATURES

- Manual choke and easy start primer give fast, reliable starts on the coldest days.
- Winter Engineered[®] to prevent ice buildup and engine shut downs.
- Cast iron cylinder sleeve for extended engine life.
- Premium mechanical governor provides positive, instant response to changing load conditions.
- High oil fill with automotive-type dipstick.
- Two-year warranty with ten years on electronic ignition.




| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-----------------|----------|---------------------------------|-----------|--------------------------------|--------------------|
| 912301B | Standard | 35701A | 18 Watt | Manual | X * | Dual Side | 6 qt. (5.7 ltrs.) Ref. 4 | 3600 |

* 37105 - 120 volt electric starter can be installed.




13.0 HORSEPOWER OVERHEAD VALVE WINTER APPLICATION

| | |
|------------------|---------------------------------------|
| MODEL | OH358SA, OHSK130 |
| HORSEPOWER | 13.0 9.7 kW |
| BORE & STROKE | 3.312 x 2.532 in. 84.13 x 64.31 mm |
| DISPLACEMENT | 21.82 cu. in. 358 cc |
| OIL CAPACITY | 28 oz. .83 ltr. |
| (APPROX.) WEIGHT | 60 lbs. 27.2 kg |
| BOLT MTG. CIRCLE | 5 & 6.5 in. 130 mm & 170 mm |



FEATURES

- † Manual choke and easy start primer give fast, reliable starts on the coldest days.
- † Winter Engineered[®] to prevent ice buildup and engine shut downs.
- † Cast iron cylinder sleeve for extended engine life.
- † Premium mechanical governor provides positive, instant response to changing load conditions.
- † High oil fill with automotive-type dipstick.
- † Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Charging System | Controls | Provisions for Electric Starter | Oil Drain | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|----------------|----------|-----------------------------|-----------------|----------|---------------------------------|-----------|-----------------------------|--------------------|
| 913300B | Standard | 35680A | 18 Watt | Manual | X * | Dual Side | 1 Gallon (3.8 ltrs.) Ref. 9 | 3600 |

* 37105 - 120 Volt electric starter can be installed.







2.0 HORSEPOWER TWO CYCLE MULTI APPLICATIONS

| | |
|--------------------|------------------------------------|
| MODEL | TM049XA, TC300 |
| HORSEPOWER | 2.0 1.49 kW |
| BORE & STROKE | 1.75 x 1.25 in. 44.43 x 31.7 mm |
| DISPLACEMENT | 3.0 cu. in.. 49.2 cc |
| OIL / FUEL MIXTURE | 24:1 |
| (APPROX.) WEIGHT | 7 lbs. 3.2 kg |



FEATURES

- Engineered for hand-held applications such as ice and earth augers, mini cultivators, tree pruners, brush cutters and power sprayers.
- Excellent starting, power and performance in cold weather.
- Electronic capacitor discharge ignition system provides starting voltage at low RPM.
- Balanced distribution of weight with minimal vibration ensures stability and durability.
- Load-responsive governor maintains engine speed during changing load conditions and prevents engine overspeeding.
- No-rust polyethylene fuel tank reduces condensation and won't dent or rust.
- Certified to EPA Phase II standards.



| Part Number | Customer | Controls | Air Cleaner Style (pg. 2) Service Part No. Ref. No. | Carburetor | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed +/- 200 | Note |
|---------------|------------------------------|----------|---|--------------------|-------------------------------|-------------------------------|------------|
| 800267 | Active Technology | Remote | 450255 (Flocked Screen) 450252 (Poly) Ref. 3 | Diaphragm w/Choke | 20 oz. (600 ml) Ref. 7 | 6000 | Long Base |
| 800268 | Flymo | Remote | 450255 (Flocked Screen) 450252 (Poly) Ref. 3 | Diaphragm w/Primer | 20 oz. (600 ml) Ref. 7 | 5500 | Short Base |
| 800269 | Flymo | Remote | 450255 (Flocked Screen) 450252 (Poly) Ref. 3 | Diaphragm w/Primer | 20 oz. (600 ml) Ref. 7 | 3800 | Short Base |
| 800302 | Feldman Ardisam Strikemaster | Remote | 450255 (Flocked Screen) 450252 (Poly) Ref. 3 | Diaphragm w/Choke | 20 oz. (600 ml) Ref. 7 | 6000 | Long Base |
| 800666 | Hoffco | Remote | 450255 (Flocked Screen) 450252 (Poly) Ref. 3 | Diaphragm w/Choke | 20 oz. (600 ml) Ref. 7 | 5200 | Short Base |





3.0 HORSEPOWER TWO CYCLE VARIOUS APPLICATIONS

| | |
|--------------------|-------------------------------|
| MODEL | TV085XA, AV520 |
| HORSEPOWER | 3.0 2.24 kW |
| BORE & STROKE | 2.09 x 1.50 in. 53 x 38 mm |
| DISPLACEMENT | 5.2 cu. in. 85 cc |
| OIL / FUEL MIXTURE | 24:1 |
| (APPROX.) WEIGHT | 13.2 lbs. 5.9 kg |
| BOLT MTG. CIRCLE | 4.0 in. 102 mm |



FEATURES

- ï Engineered for hand-held applications such as ice and earth augers, mini cultivators, tree pruners, brush cutters and power sprayers.
- ï Excellent starting, power and performance in cold weather.
- ï Electronic capacitor discharge ignition system provides starting voltage at low RPM.
- ï Balanced distribution of weight with minimal vibration ensures stability and durability.
- ï Load-responsive governor maintains engine speed during changing load conditions and prevents engine overspeeding.
- ï No-rust polyethylene fuel tank reduces condensation and won't dent or rust.
- ï Certified to EPA Phase II standards.



| Part Number | Customer | Application | Crankshaft Service No. Part No. | Controls | Air Cleaner Style (pg 2.) Service Part No. Ref. No. | Fuel Tank (pg. 3) Ref. No. | Top Governed Speed |
|-------------|----------|-------------|---------------------------------|----------|---|----------------------------|--------------------|
| 800265B | Feldman | Auger | 290634 | Remote | None | 1 qt. (.95 ltr.) Ref. 8 | 4500 |
| 800266A | Hoffco | Scythe | 290637 | Remote | 450205 (Flocked Screen) 450215 (Poly) Ref. 2 | None | 4800 |






3.0 HORSEPOWER TWO CYCLE WINTER APPLICATION

| | |
|--------------------|-------------------------------|
| MODEL | TH098SA, HSK600 |
| HORSEPOWER | 3.0 2.24 kW |
| BORE & STROKE | 2.09 x 1.75 in. 53 x 44 mm |
| DISPLACEMENT | 6.0 cu. in. 98 cc |
| OIL / FUEL MIXTURE | 50:1 |
| (APPROX.) WEIGHT | 12 lbs. 5.44 kg |



FEATURES

- ï Manual choke with remote primer for reliable starts.
- ï Moisture sealed electronic capacitor discharge ignition (CDI) system, and freeze-resistant easy-pull recoil starter.
- ï Dependable fixed speed gets you right to work.
- ï Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Provisions for Electric Start | Controls | Top Governed | Notes |
|-------------|-------------------|-----------------------------|-------------------------------|-------------|--------------|-------|
| 900390B | MTD Mont. Ward | 290609 | X * | Fixed Speed | 4700 | ▲ |
| 900392B | Toro | 290602 | X * | Fixed Speed | 4700 | ▲ |
| 900393A | Murray | 290607 | X * | Fixed Speed | 4500 | ▲ |
| 900396A | Snapper | 290602 | X * | Fixed Speed | 4500 | ▲ |

* 590556 - 120 Volt electric starter kit can be installed.

▲ Fuel tank omitted.






4.5 HORSEPOWER TWO CYCLE WINTER APPLICATION

| | |
|--------------------|-----------------------------------|
| MODEL | TH139SA, HSK845 |
| HORSEPOWER | 4.5 3.35 kW |
| BORE & STROKE | 2.437 x 1.812 in. 61.9 x 46 mm |
| DISPLACEMENT | 8.46 cu. in. 139 cc |
| OIL / FUEL MIXTURE | 50:1 |
| (APPROX.) WEIGHT | 20 lbs. 9.1 kg |
| BOLT MTG. CIRCLE | 3.625 in. 90 mm |



FEATURES


- ï Manual choke with remote primer for reliable starts.
- ï Moisture sealed electronic capacitor discharge ignition (CDI) system, and freeze-resistant easy-pull recoil starter.
- ï Dependable fixed speed gets you right to work.
- ï Two-year warranty with ten years on electronic ignition.



| Part Number | Customer | Crankshaft Service Part No. | Provisions for Electric Starter | Controls | Top Governed Speed | Notes |
|-------------|----------|-----------------------------|---------------------------------|-------------|--------------------|-------|
| 900394B | MTD | 290614 | X * | Fixed Speed | 3800 | ▲ |
| 900395 | Toro | 290681 | X * | Fixed Speed | 3850 | ▲ |
| 900397B | Service | 290627 | X * | Fixed Speed | 4000 | ▲ |

* 590670 - 120 Volt electric starter kit can be installed.

▲ Fuel tank omitted.



ENGINES & TRANSMISSIONS

TecumsehPower Company
900 North Street
Grafton, WI 53024
Phone: 262-377-2700
Fax: 262-377-4485

TecumsehPower International
152-154 Commercial Road
Staines, Middlesex
United Kingdom TW18 2QP
Phone: (44) 1 784-450785
Fax: 1784-453563

www.TecumsehPower.com